

Sales Code	Std/Opt	Description	\$ List	Weight
Model				
0000380	S	T380 Series Conventional	108,874	9,930
0070086	S	T380 Aero Hood	0	0
0080101	O	CARB Low NOX Omnibus Registration Guidelines Dealer/Customer acknowledges that this vehicle is NOT intended for registration or domicile/primary use in the State of California.	0	0
0080314	O	EPA Clean Idle Label - PACCAR PX Engines	36	0
0090143	O	T380 Automatic	0	0
0098438	O	State of Registry: Pennsylvania	0	0
Engine & Equipment				
0130219	O	PACCAR PX-9 300 300@1850 860@1200, 2024 With Turbo Exhaust Brake (VGT Brake) N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 252...Reserve Speed Function Reset N09200 C399 100...Standard Maximum Speed Limit N09400 C401 10....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 0.....Expiration Distance (C395) N09260 C121 65....Max Vehicle Speed in Top Gea N09440 C234 NO....Engine Protection Shtdwn N09460 C231 NO....Gear Down Protection N09580 C133 5.....Idle Shtdwn Time N09680 C233 NO....Idle Shtdwn Override N09480 C132 1400..Max PTO Speed N09300 C128 65....Max Cruise Control Speed N09500 C239 NO....Cruise Control Auto Resume N09520 C238 NO....Auto Engine Brake in Cruise N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold N09560 C225 NO....Enable Idle Shutdown Park Br	9,633	694
1000046	O	EPA Emissions Warranty Engine	0	0
1000151	S	PremierSpec	0	0
1000244	O	Gearing Analysis: Balance power/economy blend results.	0	0
1000254	O	Customer's Typical Operating Spd: 65 MPH	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
1000525		RegistrationYear Year of Registration: 2025	0	0
1000684	O	Effective VSL Setting NA	0	0
1000858	O	Engine Idle Shutdown Timer Disabled	0	0
1000891	O	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0	0
1002060	S	Air Compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0	0
1041399	S	Air Cleaner: MD Composite Engine Mounted	0	0
1105232	O	Fan Hub: Horton Variable Speed For use with PX engines, L9N or B6.7N natural gas engines on 2.1M only.	645	0
1121231	S	Cooling Module: 2.1M MD - Aero Hood 1000 Square Inches	0	0
1247263	O	EXH: Single Can 2024 RH Under with RH Side-of-Cab Vertical Tailpipe	3,108	0
1290130	O	Tailpipe: 5 in. single 30 in. 45 degree curved.	199	12
1321102	S	Fuel Filter: PACCAR 2.1M MD for PX-7 or PX-9 Fuel/water separator for 2021 and later engines.	0	0
1321205	O	Run Aid:Fuel Heat *For Fuel Filter	41	0
1321305	O	Start Aid:12V Heat *For Fuel Filter	22	1
1504006	O	Block Heater: PACCAR 750 watt 120V for PX-7 and B6.7N. 1000 watt for PX-9 and ISL9 Engines.	26	2
1816260	O	Alternator: PACCAR 160 amp, Brush Type	171	0
1821210	O	Batteries: 3 PACCAR GP31 Threaded Post (700-730) 2100-2190 CCA dual purpose.	179	62
1836106	O	Mitsubishi 105P55 12V Starter with Cummins and PX PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. Only for Cummins or PX engines.	35	0
1840065	S	12V Low Voltage Disconnect for Battery Protection	0	0
1840067	O	Battery Disconnect Switch Mounted on Battery Box Provides One (1) Switch	404	0
1900996	O	Jump Start Terminals Under Hood.	85	0
1901017	O	Remote PTO/Throttle, 12-Pin, Engine Bay Remote Control Provision	34	0
Transmission & Clutch				
2011613	O	Transmission: Allison 3000RDS 6-speed, With PTO drive gear. 6th Generation controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Requires a	10,298	443

Sales Code	Std/Opt	Description	\$ List	Weight
		push button shift control code. Oil temperature gauge is standard on class 8 models. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.		
2406466	O	Driveline: 2 Dana SPL170SF With 1 Centerbearing	560	84
2409941	O	One Heavy-Duty One-Piece Aluminum Crossmember This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	129	0
2410018	O	Torque Converter Included W/ Allison Transmission.	0	0
2410153	O	Push Button Shifter Controls, Center Console Mounted for Allison Transmission. 2.1m Medium Duty only.	0	0
2410204	O	Allison Fuel Sense: Delete	0	0
2410244	O	J1939 Park Brake Auto Neutral	0	0
2410310	O	Allison Neutral at Stop	0	0
2429358	O	Rear Transmission Support Springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	93	0
2429378	O	Customer Installed Transmission PTO in the LH Mounted position (8 o'clock) for Allison 3000 & 4000 transmissions.	0	0
Front Axle & Equipment				
2502230	O	Dana Spicer E-1202IL Front Axle rated 12K 3-1/2in. drop. Use W/Air Brakes Only. Medium Duty Only.	146	-321
2621310	S	Front Brakes: 14.6K Bendix ES S-Cam 16.5x5 in.	0	0
2690002	S	Front Brake Drums: 14.6K 16.5x5 in. cast.	0	0
2702500	S	Front Hub: Iron Hub Pilot 14,600 lbs. 11-1/4 in. bolt circle. For use w/ air disc brakes. Consider wheelguards (5850002) w/ aluminum wheels.	0	0
2741970	S	ConMet PreSet Plus Hub Package; Front Axle.	0	0
2750001	S	Hubcap: Front Vented.	0	0
2765001	S	Front Auto Slack Adjuster for Drum Brakes.	0	0
2864070	O	Front Springs: Taperleaf 13.2K W/ Shock Absorbers w/ maintenance-free elastomer spring pin bushings.	420	111
2895223	S	Single Power Steering Gear: 13.2K for Air Brakes.	0	0
2900055	O	5 mm Front Suspension Spacer Block	0	0
2900612	O	Threaded Front Spring Bushings in Place of elastomeric.	66	0

Sales Code	Std/Opt	Description	\$ List	Weight
Rear Axle & Equipment				
3031181	O	Single Dana Spicer S21-172 Single Reduction Rear axle. Single rear axle rated at 21K.	697	102
3200525	O	Rear Axle Ratio - 5.25.	0	0
3330004	S	Single Rear Brakes 16-1/2x7 in. Bendix ES- extended service S-cam.	0	0
3392007	S	Single Rear Brake Drums: Cast S-Cam Single For use with 15x8.625", 16.5X7" or 16.5X8.625" brake.	0	0
3403220	S	Single Rear Hubs: Iron Hub Pilot 26k; 11.25" Bolt circle. Requires "R" series outer ends.	0	0
3441971	S	ConMet PreSet Plus Hub Package; Single Rear Axle.	0	0
3465001	S	Single Rear Axle Automatic Slack Adjusters. For use with drum brakes.	0	0
3485214	O	Spring Brake: 3036 Long Stroke Single 30 Square inches; 36 square inches spring chamber. For drum brakes	90	0
3495226	S	Bendix 4S/4M Anti-Lock Brake System.	0	0
3531001	O	Wheel Differential Lock for Dana Spicer Axles S21-170/172, S21-190, S23-170/172, S23-190, S26-190 & S30-190; adds D to the end of the axle part number.	929	28
3636422	O	Rear suspension: single Reyco 79KB taperleaf 23K with helper spring. Medium-duty. Unladen Height: 9 in. Laden Height: 7.3 in. Not rear air disc brake compatible.	281	58
3836310	O	Rear Shock Absorbers for Reyco 79KB.	262	35
3836315	O	Bolted Rear Suspension Crossmembers for Reyco 79KB. Replaces medium duty standard.	322	41
Tires & Wheels				
4010137	O	Front Tires: Michelin X Line Energy Z 11R22.5 16P	627	-1
4238866	O	Rear tires: Goodyear Endurance LHD 11R22.5 16PR	1,234	80
4900004	O	Rear Tire Quantity: 4	0	0
5043550	O	Front Wheel: Alcoa ULA18 22.5x8.25 MagnaForce aluminum alloy, hub-pilot mount. 7400lb maximum rating. Air Disc Brake compatible. High polish.	373	-51
5243550	O	Rear Wheel: Alcoa ULA18 22.5x8.25 MagnaForce aluminum alloy, hub-pilot mount. 7400lb maximum rating. Air Disc Brake compatible. High polish.	746	-102
5900004	O	Rear Wheel/Rim Quantity: 4	0	0
Frame & Equipment				
6054410	O	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 309 in. to 380 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in-lbs per rail.	425	281

Sales Code	Std/Opt	Description	\$ List	Weight
		120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required, Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.		
6308715	O	Bumper: Aerodynamic Chrome Steel. Requires a bumper setting code.	1,101	68
6319040	S	40 in. Bumper Setting. Requires a Bumper Code.	0	0
6321010	S	Front Tow Loops: Two	0	0
6391202	O	Custom Frame Layout: Two Chassis CFL C/M: CLEAR 40-80" BOC	690	0
6397001	O	Huck Bolts Throughout Frame, where Possible.	0	0
6404421	O	Battery Box: Steel Parallel Module under W/Step, polished aluminum cover. Use with 2 or 3 batteries. Up to 2 air tanks may be mounted to bottom of box. Batteries will be oriented perpendicular to the frame rail in a single row.	409	9
6409901	O	Battery Box Location: LH Side.	0	0
6451125	O	DPF/SCR Box Natural End Plates and Natural cover.	0	0
6490139	O	Heavy-Duty One-PC Aluminum Intermediate/ Fill-In crossmember.	249	13
6490434	O	Heavy-Duty 5-Piece Rear Cab Support, Bolted assembly. Huck fastened to frame.	49	15
6742009	S	Square End-of-Frame W/O Crossmember; Non-Towing.	0	0
Fuel Tanks & Equip				
7144060	O	60 US Gallon D-Shape Rectangular Aluminum BOC fuel tank, replace.	-41	-21
7722170	S	Small DEF Tank, 5.5 Gallons.	0	0
7840015	O	Polish Only One Aluminum Tank.	140	0
7840038	O	Polished Cover for 1 DEF Tank Any Size.	254	3
7889007	O	Fuel Fill: Center of Tank(s) BOC. Not available on fuel tanks with 3 supports or with full or partial chassis fairings.	0	0
7889061	O	Polished Stainless Steel Tank Straps for 1 Tank.	89	0
7889206	O	Minimum Required DEF to Fuel Fill Ratio 1:1.	0	0
7889217	O	DEF capacity ratio - Truck to be centrally fueled	0	0
7889614	O	DEF Tank Location is LH BOC. For 2.1M Medium-Duty	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
7940060	O	Location: 60 gal fuel tank LH behind cab	0	0
Cab & Equipment				
8024311	S	Cab: Stamped Aluminum with Curved Windshield LED markers. Requires separate roof code.	0	0
8090154	O	Hood: Short Aero w/ Chrome Crown	124	0
8108011	S	Cab HVAC - Day Cab and 40 in. Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0	0
8201047	O	Kenworth Smartwheel: 18 in. Non-Leather With Integrated Radio and Cruise Controls.	143	0
8201200	S	Adjustable Telescoping Tilt Steering Column.	0	0
8203060	O	5 Sets of Keys. Replaces Standard 2 Sets of Keys.	34	0
8205135	O	Information for Customer-Installed PTO Muncie 10-bolt.	0	0
8205177	O	Dash Switch:1st Allison-Mounted PTO. Electric switch and wiring are factory-installed to control the 1st Allison Trans mounted PTO.	167	0
8208497	O	Four Spare Switches: Wired to Power.	103	0
8209999	O	Spare Power Wiring For Customer Installed Devices Behind Dash Cluster. Includes 2 batt, 2 ign, 1 acc, 1 LVD at 20A each.	90	2
8221105	O	Gauge: Air Application Gauge.	46	0
8222409	O	Gauge: DD Virtual Gauge - Air Filter Restriction	0	0
8222413	O	Gauge: DD Virtual Gauge - Manifold Pressure Boost	0	0
8222414	O	Gauge: DD Virtual Gauge - Engine Percent Torque	0	0
8222418	O	Gauge: DD Virtual Gauge - Engine Hours Instrument Cluster	0	0
8222419	O	Gauge: DD Virtual Gauge - Volts Instrument Cluster	0	0
8222712	O	Gauge: Fuel Filter Restriction Gauge.	134	0
8226667	O	Gauge: Oil Temperature Gauge Transmission. The NavPlus HD unit includes a virtual transmission oil temperature	52	0

Sales Code	Std/Opt	Description	\$ List	Weight
		gauge.		
8282024	S	Main Instrument Package: 7" Digital Display Cluster. Includes Physical (Analog): Speedometer, Tachometer, Oil Pressure, and Coolant Temp; and Digital: Fuel Level #1, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure, and Air Application for air brake trucks.	0	0
8330591	S	Interior Trim Package: 2.1M MD Gray Foam Backing/Cloth Headliner W/Gray Sunvisor & Seat Color Three Underdash Center Console Cupholders (Two If Allison Transmission Is Selected).	0	0
8410122	O	Driver Seat: KW Air Seat HB Vinyl w/ Dual Armrests/Susp Cover	197	0
8480232	O	Rider Seat: KW Toolbox Seat HB Vinyl w/ Dual Armrests/Record Holder/Occupancy Sensor	-145	0
8490161	O	Seat Color: Black Replacing Standard Gray	0	0
8601432	O	Kenworth Radio DEA710 AM/FM/WB/USB, Bluetooth	405	0
8698965	O	Speaker Package For Cab: (2) Speakers B-Pillar	56	0
8699933	O	CB Installation Kit: C/I Center Mtd of Header w/ Dual Antenna on LH/RH mirrors. One Jumper Harness.	231	2
8700161	O	Footwell Light: Red Lens & Switch	13	0
8700196	S	Turn Signal: Self-Cancelling	0	0
8700283	S	LH and RH Trip Ledge Rain Deflectors	0	0
8700601	S	Global Telematics Unit	0	0
8800260	O	Long Grabhandle RH Side Mounted to Side-of-Cab exhaust.	31	2
8800372	O	Grabhandle: LH, Exterior, Side of Cab - Ergonomic Grab Handle Mounted To The Left Hand Exterior Of The Cab For Entry and Exit.	121	3
8800402	S	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0	0
8832113	S	Kenworth Daylite Door With Standard LH/RH electric door locks and LH/RH electric window controls.	0	0
8841642	O	Air Horn: Dual Round 26" LH/RH Roof Incl Air Horn Cover	339	0
8850139	S	Look-Down, Pass. Door, Black 11x6	0	0
8850841	O	Mirror Shell: Dual Aero Chrome	154	0
8860852	O	Mirror: Dual KW Aero Rear View Motor, heated with Integral CX.	66	0
8871446	S	Rear Cab Stationary Window 19in x 36in	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
8890038	O	3.5in x 11.5in Plastic Records Holder:Mounted On Rear Cab Panel. Not available With Sleeper Or 2 Person Bench Seat.	54	0
8890101	S	One-Piece Bonded-In Windshield With Curved Glass. Standard.	0	0
8890135	O	Exterior Stainless Steel Sunvisor.	720	11
8890874	O	Kenworth Cab Air Suspension.	160	0
8891011	O	Roof: Raised Profile, Stamped Aluminum w/ Additional Head Room & Interior Overhead Storage	306	0
Lights & Instruments				
9010803	S	Headlamps: Single Halogen Complex Reflector w/ Turn Indicator, Reflector and DRL. Fender Mtd.	0	0
9022130	O	Marker Lights: Five Rectangular LED. Chrome housing. For use with raised roof only. Required with exterior sunvisor.	62	0
9030052	S	LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.	0	0
9058085	O	Switch,Wire,Indicator Light: C/I Flood 1st SW Thru Grommet Under Cab	129	0
9090312	O	Body Builder Lighting Harness Coiled End Of Frame For Additional Customer Installed Exterior Lighting. Harness Includes Circuits for Additional Customer Installed Tail Lamps, Turn Lamps, Stop Lamps, and Marker Lamps.	156	0
9090849	O	Polyswitches Replacing Fuses. Switch Will automatically reset after removal of excess load.	43	0
Air Equipment				
9101218	S	Air Dryer: Bendix AD-HF Puraguard Heated	0	0
9108001	S	Moisture Ejection Valve W/ Pull Cable Drain.	0	0
9140020	S	Nylon Air Tubing in Frame & Cab, Excluding Hoses subject to excessive heat or flexing.	0	0
Extended Warranty				
9200008	O	Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0	0
9200022	S	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0	0
9210402	O	Allison 3000 Series Transmission Surcharge	700	0
9212661	O	TruckTech+ RD - 5YR Sub PACCAR PX Engines	799	0
9220001	O	Base Warranty: Emissions 5YR/100K MI - EPA Engine	0	0
Miscellaneous				
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0	0

Sales Code	Std/Opt	Description	\$ List	Weight
9490206	O	Warning Triangle Reflector Kit: Shipped Loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	58	4
9490404	O	One 5 lb. Dry Chemical Type Fire Extinguisher mounted outboard of driver seat. Class ABC.	136	11
9491652	S	EMUX Architecture	0	0
Promotions				
9511124	O	Model Year 2025 Engine	0	0
Paint				
9700000	O	Paint Color Number(s). N9702 A - L0006 WHITE N9720 FRAME N0001 BLACK	0	0
9943004	S	Bumper Unpainted	0	0
9943048	O	Day Cab Bulk Paint	0	0
9943050	S	Day Cab Standard Paint	0	0
9944820	S	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0	0
9965510	S	Base Coat/ Clear Coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0	0

Special Requirements

- Special Requirement 1 0098025
- Special Requirement 2
- Special Requirement 3
- Special Requirement 4

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$148,315
Marketing and Service Support Fee	\$845
Prepaid Freight	\$3,775
Total Surcharge/Options Not Subject To Discount	\$1,499
Total Weight (lbs)	11,611

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity	Beginning Chassis	Ending Chassis
Liquid Measurement Controls Inc. 126 Industrial Parkway Pottstown, Pennsylvania 19464	2	216369	216370