

# **Freightliner Tank Truck Quotation**

### **Customer: STOCK SPECIFICATION Attention:**

Quote #:

Date:

1 December 2024

#### **Tank Specifications**

Tank Material:	Aluminum – 5454 Alloy Nu			Num	nber of Compartments: TWO		
<b>Compartment Sizes</b> (Nominal Front to Rear)	1	2000	80	00			
Bulkheads:	Single				Canopy:	35" With Met	er Box Cover
Bottom Loading / Vapor Recovery <mark>OPTION \$12K</mark>	Two Compartment Aluminum Manifold / Openable API Adapters / Thermistor Overfill System & Socket / Ground Bolt & Ball / Roto Product Markers - ULSD C & D / HO / Gas						

#### **Pumping System Specifications**

Meter:	Liquid Controls M-7-CLI-1 2" Aluminum Meter with Combination High-			
	Capacity Strainer & Optical Air Eliminator / LCR II Register System with			
	E-7 Valve / Epson Slip Printer on Cab Pedestal			
Multi-Wrap	Hannay Inverted Hose Reel with Explosion-Proof Motor, Comet Drag &			
Hose Reel:	Air Caliper Brake tied into PTO / 150' x 1 3/8" Goodyear Redwing hose			
	with Scully Nozzle with Unifil End			
Gravity Drop /	None			
Suction Pump-Out:				
Quick Drop /	None			
Metered Discharge:				
Pumping Speeds:	High	Low		
Manual & Automatically Controlled	68	50		

Tanks are manufactured by TREMCAR at their U-Stamp Certified, D.O.T. registered facility in Saint-Jean-sur-Richelieu,, QC CN. They are built to meet or exceed all D.O.T. 406 standards and are unsurpassed in strength, head size options and integrity. All Tank Trucks completed by Liquid Measurement and Controls, Inc. are fully inspected, pump tested and are ready to be put into service upon delivery. Pump testing and meter calibration are included in the standard package.



#### **Tank Features**

Semi-Rectangular, Canopy Style Tank	Die Pressed, Deep Dished & Flanged Heads
Aluminum Jeep Style Fenders with Mud Flaps	Expanded Aluminum Walkway on Top of Tank
Built to Meet or Exceed D.O.T 406 Code	"VIK" stickers & 406 Plate
Betts 16" Manholes with 10" Fills & Vents	(4) Flashing Amber Lights Rear Head Switch in Cab
Tank Capacity Markers in Each Compartment	Rear Tank Drains with Shutoff Valves in Canopy
(4) Placards to customer requirements	DOT 406 Steel Bumper Wrapped in Extruded Aluminum
Betts LED Lighting Mounted in Rear Canopy Head	Sealed Beam Back-up Lights
Bumper Hose Roller Curb Side	Nozzle Holder with Drain
Dipstick & Underground Fill Holder	Rear Aluminum Ladder
Flex, Security Mounting & Neoprene Sills	16" x 16" x 32" Aluminum Tool Box Curb Side

# System Features

3" Pneumatic Tank Valves	Hose Reel Tied To Parking Brake –	
	Released Hose Reel Locked / Engaged Hose Reel Free	
Scully Mark IV Check Valve with 2-Stage Pneumatic	150' of 1 3/8" Goodyear Redwing Hose with Scully 1.5"	
Pump Speed Control	Unifil Nozzle	
2.5" Blackmer Pump with Pneumatic Bypass	All Aluminum Piping	
	Hot-Shift PTO Mounted in Meter Box	
Meter Pressure Gauge	Back-up Alarm	

## **Optional Items Installed**

MyMobileVision SMS7001 7" LCD Camera Installed	INCLUDED
(4) Flashing Amber Lights Rear Head Switch in Cab	INCLUDED

\$190,000.00	Tremcar Tank & Equipment Mounted on 2024 M2 per specification		
\$0.00	Federal Excise Tax – NONE		
\$0.00			
\$0.00	\$10,000 Deposit To Hold Unit		
\$190,000.00	Completed Balance Due		
TERMS: THIS QUOTATION IS FOR IMMEDIATE ACCEPTANCE AND SUBJECT TO CHANGE WITHOUT NOTICE. PRICING IS FOB			
	POSIT IS DUE WITH ACCEPTANCE AND THE BALANCE IS DUE UPON COMPLETION. COMPLETED		
UNITS ARE TO BE PICKED UP WITHIN FIVE WORKING DAYS OF COMPLETION OR PENALTIES MAY ACCRUE. THE PRICE			
DOES NOT INCLUDE ALTERATIONS TO THE CHASSIS OR ITEMS NOT SPECIFICALLY OUTLINED IN THE QUOTATION. AN			
EXPRESS MECHANICS LEIN IS HEREBY ACKNOWLEDGED ON THIS UNIT TO SECURE THE AMOUNT OF THE QUOTATION.			
THE TANK IS DESIGNED FOR PETROLEUM PRODUCTS. IT IS THE RESPONSIBILITY OF THE OPERATOR NOT TO EXCEED			
THE G.V.W. RATING OF TH	E CHASSIS OR D.O.T. HIGHWAY WEIGHT REGULATIONS.		
Quotation Acceptance:			
Signatures	Date		